

# Networkable Paperless Data Acquisition System



RD8300 Series  
Starts at

**\$2395**



- ✓ 6 or 12 Universal Inputs
- ✓ Up to 4 Pulse/Frequency Inputs
- ✓ 6 or 12 Relay Outputs
- ✓ Networkable Using Standard Ethernet Port
- ✓ 21 CFR Part 11
- ✓ 24V Transmitter Power Supply
- ✓ NEMA 4 (IP65) Compliant
- ✓ Locking Media Access Door
- ✓ Onboard Media Drives:
  - CompactFlash™
  - USB (Memory Stick, External Drive, etc.)
  - Smart Digital (SD)
- ✓ Touch Screen Control
- ✓ Direct on Screen Chart Annotation with Integral Stylus
- ✓ Infrared Port
- ✓ Built in OPC Server
- ✓ Built in E-mail Client
- ✓ Shallow Installation Depth 165 mm (6.5")

## Benefits

- ✓ Maximum Flexibility Achieved with Universal Inputs
- ✓ Input Pulse Signals Directly from Flow Meters
- ✓ Relay Outputs for Control or Activating Alarms
- ✓ Accessible via LAN or WEB
- ✓ Reduce Cost and Complexity by Providing Transmitter Power Supply
- ✓ No Additional Equipment



RD8312, \$2695, shown smaller than actual size.

Locking media access door closed.

## Needed for Harsh Environments

- ✓ Media and Data Can Be Locked and Secured
- ✓ Flexibility of Multiple Media Drives
- ✓ Intuitive Icon Driven Touch Screen
- ✓ Write Notes and Comments Directly on Chart for Permanent Storage with Data
- ✓ Remote Control Wirelessly
- ✓ Seamlessly Interfaces with Third Packages Using OPC Standard
- ✓ Send Alarm, Instantaneous Data or Information Anywhere with E-Mail
- ✓ Shallow Depth Allows the Use of Economical and Enclosures for Installation

The RD8300 is the most advanced

paperless recording system available. It incorporates the latest in measurement, communication, interface and processing technologies to deliver unmatched performance for your data acquisition application.

The RD8300 series utilizes a high contrast 142 mm (5.6") color Active Matrix TFT LCD display with a rugged touch screen. Use a finger or the onboard stylus, if you prefer, to perform data entry and system navigation. The front panel is also fully compliant to IP65 for use in dusty or wet areas. An intuitive icon driven menu system guides the user through easy to follow setup and control screens. The display builder feature makes setting up custom screens extremely simple. Design up to 50 custom displays containing various combinations of indicator types such as horizontal and vertical bar graphs, large and small digital indicators and horizontal or vertical trends. On-screen help is available throughout the menu system to assist you during setup and use.



Intuitive System Menu

Main Menu Setup




Windows® Explorer Menu




Custom Designable Display Screens


Display Builder




Horizontal Trend



Horizontal Trend with Indicators



Vertical Trend with Bar Graphs




Digital Indicators with Bar Graphs




Vertical Trend



Channel Setup



On-Screen Help



Display Screen Rotation Setup



When it comes to storing data, the RD8300 is extremely flexible. Data can be stored to the non-volatile internal flash RAM or any of the available storage drives including CompactFlash™ and USB provided there is media present. Programmable record start and stop times allow the user to start and stop recording at predetermined intervals. Data may also be stored to a remote PC via Ethernet using the optional Exhibitor Software. In addition, the built in OPC Server allows any OPC compliant software

client to connect to, communicate with and retrieve data. The RD8300 utilizes many layers of security to protect the integrity of your stored data. All data is stored in an encrypted binary format which prevents data tampering and maximizes compression. The front access media door is lockable to prevent unauthorized access to the internal removable storage media. There are 3 levels of password protection to prevent unauthorized entry into critical recorder function menus. To ensure that data files are

completely error free the RD8300 has a built-in rechargeable Nickel Metal Hydride battery backup system that constantly monitors the incoming power source. In the event of a power loss or power dip, the RD8300 seamlessly switches over to the internal power and begins a safe and controlled system shutdown. When power is restored the recorder immediately returns to the last state of operation. This guarantees that data files will never be corrupted by unexpected power conditions.

## Recording Data



Calendar

## Removable Media Types



Memory Card

USB Memory Stick

SD (Internal)

## Write Directly On the Screen



Make notes, sign files or make other graphic indications directly on the virtual chart in your own handwriting, or use the built-in keyboard to type messages on the screen. Your notes are stored within the data file directory for future review.




The innate feature of handwriting notes and comments on the chart of paper recorders had been lost with the onset of video graphic recorders until the arrival of the RD8300. Using the high-resolution touch screen interface and the integral stylus you can once again make notes or comments directly on the chart. This on-screen annotation is stored within the data file directory and can be recalled and displayed on the recorder or in Exhibitor Software.



Calculator

### Powerful Math Package

The onboard math package is extremely powerful. It allows the user to input complex polynomial equations using constants, custom functions and variable inputs obtained from live channels. The resultant information can be displayed and recorded as a real time channel. Using the intuitive calculated channel setup menu the user enters in the formula and can perform a test to make sure the formula is accurate.



Play unique sound files for each alarm by simply selecting the file you want to play when you set up the alarm.

### Unique Sounds

Unique .wav files may be uploaded and played through the internal speaker to alert of specific types of alarms. Use any .wav file, even customize your own spoken word announcements. In areas where there is a high level of ambient noise the alarm .wav files can be output to a P.A. system or amplified speakers via the rear mounted audio connector. Each alarm setpoint can have a unique sound file associated with it. In the alarm setup menu simply select the .wav file you want to play when the alarm is active.

### Remote Control

The remote control feature extends the graphic user interface of the RD8300 Series directly onto your local PC. Use remote control and your desktop PC's mouse and keyboard to view real time data, change settings, start and stop recording or virtually anything else you can do with the recorders touch screen. Across the plant or across the planet, remote control empowers you with virtual presence.

Using the record setup menu, the user can select which channels to record, the sample storage rate, whether to record alarms and/or events, and the start/stop time and date for the record session. The location of the data file is selected in this menu along with the data file name. The user can also configure the unit to start or stop recording on an alarm level or an externally triggered input.


### Media Storage Locations

#### Front Accessible (Lockable):

CompactFlash™, USB host (for memory stick)

**Rear Accessible:** USB host, Ethernet

**Internal:** 128 MB standard (larger sizes available)



### Exhibitor Software Network Overview

Exhibitor Software is an extremely powerful set of tools that compliments the RD8300 and other OPC compliant devices. Incorporating functions to simplify

data management via searching, reviewing, printing, or exporting historic data, Exhibitor Software allows real-time monitoring and recording independently as well, while historic recording is not affected. Also featured is the OPC

Client which enables the user to build custom screens selecting various display elements and data from multiple OPC Servers, including devices other than RD8300's. (Windows™ XP/2000 Compatible).

## Customizable Real-Time View

Use Exhibitors design page features to create custom real time display projects that can be saved and recalled with a click of the mouse. Create bar graphs, digital panel meters, thermometers or trend screens from live data coming from any RD8300 or other OPC compliant device accessible on the network. Using the OPC device manager, Exhibitor allows you to connect to OPC servers anywhere there is a network connection. A user definable list of data is then accessible by the design page, where customized real-time displays are built using the user friendly graphic user interface. To place items, simply point, clicks, and drags. Save your project for future use and the next time it is opened all servers are automatically connected and data will begin displaying immediately. Go one step further, and record real time data to your PC.




Real Time Screen




Select the type of control to be displayed then customize its size, color and location.

## Graphical Review

The composite graphical view can display all inputs and calculated data from a particular recording session. The user is able to manipulate the graph to make it easy to see interaction between recorded channels, turn channels off and on, change color schemes, expand, compress, zoom, and print. Individual channels can be displayed for detailed analysis. There is a summary function for the individual channels which provides minimum, maximum, averages and time and date for the records. The same analysis tools used for the multi-channel graph are used to scroll through data, zoom, review and expand the single channel graphs.



Graphical Review Chart



Tabular Data Screen

## Tabular Data Review

The data table view displays recorded data in tabular format. All recorded information within a file can be viewed or deselected along with time stamps. Using the one click export feature, the table can be exported to Excel™ in its entirety or in portions. The data table and graph can be synchronized so that they are interactive during analysis of records. Double clicking a value in the data table will automatically bring you to the graph page with that value and time highlighted. Move the cursor over the point and detailed information is provided. Also available are separate alarm, event, and memo review screens. Memo review lists all on-screen annotations in a record.

## Specifications

**Input Resolution:** 0.0015% of full scale, 16 bit unless otherwise stated

**Input Impedance:** >1 MΩ

**Input Channels:** 6 or 12 direct input plus 6 additional calculated channels

**Maximum Input:** 50 Vdc

**Isolation:**

**Channel to Channel:** 350 Vdc or RMS AC

**Channel to Chassis:** 2000 Vdc or RMS AC

**Isolation Category II:** Pollution Degree 2

**Measurement Rate:** 10 times per second on all direct input channels

**Common Mode Noise Rejection:** >100 dB, 50/60 Hz, filter enabled

**Normal Mode Noise Rejection:** >50 dB at 50/60 Hz, filter enabled

**Math Functions:** Fully programmable +, -, x, /, square root, sine, cosine, tangent, log, totalization, powers, averages, conditional logic; AND, NOT, OR, +, >, <, gated timers; can use live channels in calculation; can define 6 constants and 6 functions per channel

## Analog Inputs

**DC Voltage:** ±125 mV, ±250 mV, ±500 mV, ±1.00V, ±3.0V, ±6.0V, ±12.0V, ±24.0V

**Accuracy:** Ranges to 1V ±0.06%, Ranges > 1V ±0.1%

**DC Current:** 4 to 20 mA, 0 to 20 mA, 10 to 50 mA

**Accuracy:** ±0.15% using external 50 Ω 0.1% ¼ watt shunt

**Thermocouple (Per ITS90):**

**Resolution:** 0.1°C, thermocouple burnout detection: automatic

**Reference Junction Compensation**

**Accuracy:** ±2.5°C (0 to 50°C)

**Data Storage Capacity:** Data stored in non-volatile RAM and recorded automatically to:

**Removable Media Types:**

CompactFlash™ or USB drive to 4 GB

**Internal Media Type:** SD card (secure digital) to 4 GB

**File Types:** Data files, alarm and event files, configuration files, language files, multiple files of different names on a single disk

## Display

**Type:** Color CCFL backlit active matrix TFT liquid crystal display

**Size:** 142 mm (5.6") diagonal

T/C Type	Range (°C)	Accuracy (°C)	Range (°F)	Accuracy (°F)
J	-210 to -100°C	±2.5°C	-340 to -150°F	±5°F
	-100 to 1200°C	±1.5°C	-150 to 2190°F	±3°F
K	-270 to -100°C	±2.5°C	-450 to -150°F	±5°F
	-100 to 1372°C	±1.5°C	-150 to 250°F	±3°F
T	-270 to -100°C	±2.5°C	-450 to -150°F	±5°F
	-100 to 400°C	±1.5°C	-150 to 750°F	±3°F
E	-270 to -100°C	±2.5°C	-450 to -150°F	±5°F
	-100 to 1000°C	±1.5°C	-150 to 1832°F	±3°F
N	-270 to -100°C	±2.5°C	-450 to -150°F	±5°F
	-100 to 1300°C	±1.5°C	-150 to 2372°F	±3°F
S	-50 to 1768°C	±3°C	-58 to 3200°F	±6°F
B	0 to 1820°C	±4°C	32 to 3300°F	±7°F

## RTD

**Base Accuracy:** 0.2% or 0.5°C (1°F)

**Resolution:** 0.1°C, 2 or 3 wire connection; cable compensation to +50 Ω, open and short circuit detection

**Resolution:** 320 W x 240 H pixels

**Interface:** Resistive analog touch screen control

**Display Builder:** Allows user to create custom displays

RTD Type	Range (°C)	Range (°F)
100 Ω Pt 385	-220 to 85°C	-364 to 1560°F
100 Ω Pt 392	-180 to 820°C	-292 to 1500°F
200 Ω Pt 385	-220 to 400°C	-364 to 750°F
200 Ω Pt 392	-180 to 400°C	-292 to 750°F
100 Ω Ni	-70 to 300°C	-94 to 570°F
120 Ω Ni	-70 to 300°C	-94 to 570°F
1000 Ω Ni	-60 to 209°C	-76 to 408°F
10 Ω Cu	-70 to 170°C	-94 to 338°F*

\* 0.5% ±0.5°C

## Frequency Inputs (2 or 4 Channels):

**Range:** 0 to 5000 Hz all channels, 0 to 10,000 Hz 1 channel

**Accuracy:** 0.005% ±1 digit

## Recording

**Recording Rates:** User programmable from 10 samples per second to 1 sample every 24 hours

**Data Format:** Proprietary encrypted format, user file naming

**Display Modes:** Graphic trending (vertical or horizontal), bar graphs (vertical or horizontal), digital meter (large or small), alphanumeric alarm and event log

**Virtual Chart Speed:** Programmable from 10 mm/hr to 10,000 mm/hr (0.5 inch/hour to 600 inches/hour)

**Display Windows:** Time/date, graphics (bars, large digital, trends) disk status, system status, menu button bar, unit identification, alarms/events



## Communications

**Network:** 10/100 Base T Ethernet per 802.3, RJ45 connection

**Servers:** Webserver supports http and ftp protocols, OPC Modbus over ethernet server

**Serial:** Isolated RS485/RS232 Modbus® interface (option)

## Power

**Requirements:** 100 to 240 Vac, 50/60 Hz; 35 VA max optional ±15%

**Power Fail Protection:** Programmed parameters stored in non-memory; clock battery backed; internal battery backup provides shutdown and the ability to survive brownouts and short blackouts seconds)

**Power Output:** Optional isolated 24 Vdc @ 120 mA output

## Input/Output

**Digital I/O:** 6 or 12 relay outputs, form A (normally open SPST contacts) rated at 200 Vdc @ 0.5 A max, 2 digital control inputs +5 to +12 Vdc @ 20 mA (optional), control inputs may be used for record start/stop, alarm acknowledge and channel reset functions

## Safety and Environmental

### Operating Range:

**Protection:** IP65 when mounted in panel

**Safety:** Meets the requirements accordance of EN61010-1 when installed in accordance with the instructions in the manual


**UL and cUL:** Pending

**EMC:** Meets the requirements of EN61326.2003 and CE directive 89/336/EEC




**Weight:** Approximately 3.17 kg (7 lb)

### Standard Features

- 142 mm (5.6") color QVGA TFT LCD display with touch screen and integral stylus
- CompactFlash™ drive (front), USB thumb drive port (front)
- USB master (rear), USB slave (rear), Internal memory
- Mouse/keyboard connection (rear)
- Audio: line in, line out, microphone (rear)
- RJ45 ethernet port (rear)
- NEMA 4 (IP65) front bezel with locking media drive door



Front and Rear Locking Bar Installation



<b>To Order (Specify Model Number)</b>		
<b>Model No.</b>	<b>Price</b>	<b>Description</b>
<b>RD8306</b>	<b>\$2395</b>	6 universal inputs, 6 math channels, 100/240 Vac, 128 MB internal memory
<b>RD8306-DC</b>	<b>2550</b>	6 universal inputs, 6 math channels, 12 to 24 Vdc, 128 MB internal memory
<b>RD8306-ST</b>	<b>2420</b>	6 universal inputs, 6 math channels, 100/240 Vac w/screw terminals, 128 MB internal memory
<b>RD8306-R6</b>	<b>2595</b>	6 universal inputs, 6 math channels, 100/240 Vac, 128 MB internal memory, 6 form A relay, 0.5 A @ 200 Vdc, 2 control inputs
<b>RD8306-R12</b>	<b>2695</b>	6 universal inputs, 6 math channels, 100/240 Vac, 128 MB internal memory, 12 form A relay, 0.5 A @ 200 Vdc, 2 control inputs
<b>RD8306-C24</b>	<b>2545</b>	6 universal inputs, 6 math channels, 100/240 Vac, 128 MB internal memory, RS232/485 serial communication
<b>RD8306-XP</b>	<b>2495</b>	6 universal inputs, 6 math channels, 100/240 Vac, 128 MB internal memory, 24 Vdc, 120 mA transmitter power supply
<b>RD8306-2GB</b>	<b>2595</b>	6 universal inputs, 6 math channels, 100/240 Vac, 2 GB internal memory
<b>RD8306-2GB-R12-C24-XP</b>	<b>3145</b>	6 universal inputs, 6 math channels, 100/240 Vac, 2 GB internal memory, 12 form A relay, 0.5 A @ 200 Vdc, 2 control inputs, RS232/485 serial communication, 24 Vdc 120 mA transmitter power supply
<b>RD8312</b>	<b>2695</b>	12 universal inputs, 6 math channels, 100/240 Vac, 128 MB internal memory
<b>RD8312-DC</b>	<b>2850</b>	12 universal inputs, 6 math channels, 12 to 24 Vdc, 128 MB internal memory
<b>RD8312-ST</b>	<b>2720</b>	12 universal inputs, 6 math channels, 100/240 Vac with screw terminals, 128 MB internal memory
<b>RD8312-R6</b>	<b>2895</b>	12 universal inputs, 6 math channels, 100/240 Vac, 128 MB internal memory, 6 form A relay, 0.5 A @ 200 Vdc, 2 control inputs
<b>RD8312-R12</b>	<b>2995</b>	12 universal inputs, 6 math channels, 100/240 Vac, 128 MB internal memory, 12 form A relay, 0.5 A @ 200 Vdc, 2 control inputs
<b>RD8312-C24</b>	<b>2845</b>	12 universal inputs, 6 math channels, 100/240 Vac, 128 MB internal memory, RS232/485 serial communication
<b>RD8312-XP</b>	<b>2795</b>	12 universal inputs, 6 math channels, 100/240 Vac, 128 MB internal memory, 24 Vdc, 120 mA transmitter power supply
<b>RD8312-2GB</b>	<b>2895</b>	12 universal inputs, 6 math channels, 100/240 Vac, 2 GB internal memory
<b>RD8312-2GB-R12-C24-XP</b>	<b>3445</b>	12 universal inputs, 6 math channels, 100/240 Vac, 2GB internal memory, 12 form A relay, 0.5 A @ 200 Vdc, 2 control inputs, RS232/485 serial communication, 24 Vdc, 120 mA transmitter power supply

*Comes with complete operator's manual.*

**Ordering Example:** *RD8306-ST, 6 universal inputs, 6 math channels, 100/240 Vac with screw terminals, 128 MB internal memory, \$2420. RD8312-R12, 12 universal inputs, 12 form A relay, \$2995.*

<b>Options (Field Installable)</b>		
<b>Model No.</b>	<b>Price</b>	<b>Description</b>
<b>RD8300-6CH</b>	<b>\$350</b>	6 channel adder module with connectors
<b>RD8300-R6</b>	<b>250</b>	6 form A relay output module with connectors
<b>RD8300-R12</b>	<b>350</b>	12 form A relay output with connectors
<b>RD8300-XP</b>	<b>150</b>	24 Vdc transmitter power supply module with connector
<b>Accessories</b>		
<b>RD8300-SW</b>	<b>\$249</b>	Windows® XP/Vista compatible software program
<b>RD8300-21CFR-CS</b>	<b>N/C</b>	21CFR p.11 compliance statement
<b>RD8300-21CFR-CDP</b>	<b>500</b>	21CFR p.11 compliance documentation package
<b>RD8300-NIST</b>	<b>600</b>	NIST traceable certificate of calibration with documentation
<b>RD8300-50OHM</b>	<b>10</b>	50 Ω external shunt resistor 0.1% accuracy
<b>RD8300-NYLONCC</b>	<b>95</b>	Padded nylon carrying case with shoulder strap
<b>RD8300-CFCR</b>	<b>50</b>	Compact flash card reader for USB connection
<b>RD8300-AUDIOSPLITTER</b>	<b>45</b>	Splitter for audio port (includes cable)
<b>RD8300-KEYSPLITTER</b>	<b>45</b>	Splitter for keyboard and mouse port (includes cables)
<b>RD8300-STYLUS</b>	<b>10</b>	3 pack of stylus
<b>RD8300-KEYS</b>	<b>10</b>	Replacement media flap key (pair)
<b>RD8300-256MBCF</b>	<b>40</b>	256 MB compact flash card
<b>RD8300-512MBCF</b>	<b>60</b>	512 MB compact flash card
<b>RD8300-1GBCF</b>	<b>75</b>	1 GB compact flash card
<b>RD8300-2GBCF</b>	<b>100</b>	2 GB compact flash card

# omega.co.uk<sup>®</sup>

Your One-Stop Source for Process Measurement and Control!

Freephone 0800 488 488 | International +44(0) 161 777 6622 | Fax +44(0) 161 777 6622 | Sales@omega.co.uk

[www.omega.co.uk](http://www.omega.co.uk)



#### UNITED STATES

[www.omega.com](http://www.omega.com)

1-800-TC-OMEGA  
Stamford, CT.

#### CANADA

[www.omega.ca](http://www.omega.ca)

Laval(Quebec)  
1-800-TC-OMEGA

#### GERMANY

[www.omega.de](http://www.omega.de)

Deckenfronn, Germany  
0800-8266342

#### UNITED KINGDOM

[www.omega.co.uk](http://www.omega.co.uk)

Manchester, England  
0800-488-488  
+44-(0)161-777-6611

#### FRANCE

[www.omega.fr](http://www.omega.fr)

0800-466-342

#### BENELUX

[www.omega.nl](http://www.omega.nl)

0800-099-33-44



## More than 100,000 Products Available!

### • Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders, Relative Humidity Measurement Instruments, PT100 Probes, PT100 Elements, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples, Thermowells and Head and Well Assemblies, Transmitters, Thermocouple Wire, RTD Probes

### • Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

### • pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

### • Data Acquisition

Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485, Ethernet and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

### • Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Pressure Transmitters, Strain Gauges, Torque Transducers, Valves

### • Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters